



Technical Specifics

Gama produktów		iCOOL
Linia		iCOOL_HFC
Model		OCU-KRE025M05
Zastosowanie		MT
Czynniki chłodnicze		R448A
Wymiary	Szerokość	1000 mm
	Wysokość	605 mm
	Głębokość	450 mm
Waga		70,00 kg
Połączenia	Ssanie	12,70 mm
	Płyn	9,52 mm
Poziom hałasu (ciśnienie akustyczne) 10 m dB(A)		43 dB
Zasilanie		220-240/1/50
Kategoria PED		I
Temperatura parowania	Maks.	0 °C
	Min.	-15 °C
Temperatura otoczenia	Maks.	43 °C
	Min.	-20 °C
Przyłącze parownika		Multiple
Maks. zalecana odległość rurociągów		30,00 m

Technical Specs Report



Maksymalna różnica wysokości (w pionie)	Parownik powyżej	7,00 m
	Parowacz poniżej	7,00 m

Chosen Specifics

Wymagane całkowite obciążenie	2000 W
Wymagana część całkowitego obciążenia	1,28
Maks. Wydajność	2554 W
Minimalna wydajność	820 W
Temperatura parowania	-10 °C
Temperatura otoczenia	32 °C
Wilgotność	85,00 %

Terms and Conditions

The software solutions within the online platform from which this printout is taken are provided with the aim of guiding the user(s) with the selection, configuration, expected performance, and operation of the systems detailed within. It is the users' responsibility to verify that all working conditions, installation, and technical requirements are applied within the software. The software provides results based on fixed criteria, and installations to which the systems are installed/applied may be subject to a wide variety of conditions. It is the users' responsibility to check and verify all conditions to which the systems are expected to operate in accordance with the required design criteria.

The software solutions should not be considered in isolation with respect to the correct installation and application of the systems. The user(s) must consult the latest available technical and commercial documentation for a complete overview and understanding of the system requirements. Where user(s) require the use of alternate third-party software for calculations, or design results in addition to, or in substitute of the software solutions offered herein, the user(s) must ensure that Panasonic has been consulted accordingly.

Panasonic holds no responsibility for any incorrect operation or selection where configurations do not meet with the required design criteria resulting from incorrect application within the software or where the user has not consulted all available supporting documentation. For the avoidance of doubt, the user(s) should consult the local Panasonic sales office or reseller for support and guidance when applying the design.

Following the design requirements within this online tool does not constitute compliance with warranty conditions, and warranty conditions may vary from region to region. Please consult the local Panasonic sales office or reseller for the latest warranty requirements relevant to the region to which the systems will be installed. Panasonic reserves the right to correct, amend, modify, or update the contents of the software solutions at any time.

All software on the platform is provided "as is" without any warranty or guarantee of any kind. In particular, Panasonic does not warrant that the operation of the software and its performance will be error-free or uninterrupted or that the software is fit for a particular purpose. Any results or data obtained from the software on this platform are for informational purposes only, and Panasonic assumes no responsibility for the correctness or accuracy of any such data or results. By printing and sharing this document, you are accepting the conditions of use. Panasonic reserves the right to change the contents of this platform, and the software provided on it at any time and without notice.

iCORE & iCOOL - list of customizable models with available configuration coding

iCORE range – CO ₂ condensing units									
Series	Application	Base model	Former model name	Customization options					MODEL
				Coating (C)	Heat recovery (D)	HP Fan (P)	Suction PRV (S)	Housing (H)	
iCORE OCU-CRC	MT/LT	OCU-CRC060A08	iCOOL CO2 7 MT/LT	✓	Base model. No options chosen.		—	Standard	OCU-CRC060A08
				—	Not available	—	—		OCU-CRC060A08-C
				✓		✓	—		OCU-CRC060A08-P
				✓		✓	—		OCU-CRC060A08-CP
		OCU-CRC150A08	iCOOL CO2 S15 MT/LT	Base model. No options chosen.					OCU-CRC150A08
				✓	—	Not available	—	Standard	OCU-CRC150A08-C
				—	✓		—		OCU-CRC150A08-D
				—	—		✓		OCU-CRC150A08-S
				✓	✓		—		OCU-CRC150A08-CD
				✓	—		✓		OCU-CRC150A08-CS
	MT	OCU-CRC210M08	iCOOL CO2 22 MT	Base model. No options chosen.					OCU-CRC210M08
				✓	Not available	Not available	Not available	Standard	OCU-CRC210M08-C
iCORE SCU-CRC	MT/LT	SCU-CRC150A08	iCOOL CO2 MAX 15 MT/LT	Base model. No options chosen.					SCU-CRC150A08
				✓	—	Standard	Not available	Standard	SCU-CRC150A08-C
				—	✓				SCU-CRC150A08-D
				✓	✓				SCU-CRC150A08-CD
iCOOL range – HFO/HFC condensing units									
iCOOL OCU	MT	OCU-KRC045M08	iCOOL 4,5 MHP	Base model. No options chosen.					OCU-KRC045M08
				✓	—	—	Not available	Standard	OCU-KRC045M08-C
				—	✓	—			OCU-KRC045M08-D
				—	—	✓			OCU-KRC045M08-P
				✓	✓	—			OCU-KRC045M08-CD
				✓	—	✓			OCU-KRC045M08-CP
				—	✓	✓			OCU-KRC045M08-DP
				✓	✓	✓			OCU-KRC045M08-CDP
		OCU-KRC070M08	iCOOL 7 MHP	Base model. No options chosen.					OCU-KRC070M08
				✓	—	—	Not available	Standard	OCU-KRC070M08-C
				—	✓	—			OCU-KRC070M08-D
				—	—	✓			OCU-KRC070M08-P
				✓	✓	—			OCU-KRC070M08-CD
				✓	—	✓			OCU-KRC070M08-CP
				—	✓	✓			OCU-KRC070M08-DP
				✓	✓	✓			OCU-KRC070M08-CDP
		OCU-KRC100M08	iCOOL 10 MHP [A-01]	Base model. No options chosen.					OCU-KRC100M08
				✓	—	—	Not available	Standard	OCU-KRC100M08-C
				—	✓	—			OCU-KRC100M08-D
				—	—	✓			OCU-KRC100M08-P
				✓	✓	—			OCU-KRC100M08-CD
				✓	—	✓			OCU-KRC100M08-CP
				—	✓	✓			OCU-KRC100M08-DP
				✓	✓	✓			OCU-KRC100M08-CDP
		OCU-KSC120M08	iCOOL 12 MHP	Base model. No options chosen.					OCU-KSC120M08
				✓	—	—	Not available	Standard	OCU-KSC120M08-C
				—	✓	—			OCU-KSC120M08-D
				—	—	✓			OCU-KSC120M08-P
				✓	✓	—			OCU-KSC120M08-CD
				✓	—	✓			OCU-KSC120M08-CP
				—	✓	✓			OCU-KSC120M08-DP
				✓	✓	✓			OCU-KSC120M08-CDP
		OCU-KSC150M08	iCOOL 15 MHP	Base model. No options chosen.					OCU-KSC150M08
				✓	—	—	Not available	Standard	OCU-KSC150M08-C
				—	✓	—			OCU-KSC150M08-D
				—	—	✓			OCU-KSC150M08-P
				✓	✓	—			OCU-KSC150M08-CD
				✓	—	✓			OCU-KSC150M08-CP
				—	✓	✓			OCU-KSC150M08-DP
				✓	✓	✓			OCU-KSC150M08-CDP
		OCU-KSC160M08	iCOOL 17D MHP	Base model. No options chosen.					OCU-KSC160M08
				✓	—	—	Not available	Standard	OCU-KSC160M08-C
				—	✓	—			OCU-KSC160M08-D
				✓	✓	—			OCU-KSC160M08-CD
		OCU-KSC190M08	iCOOL 21D MHP	Base model. No options chosen.					OCU-KSC190M08
				✓	—	—	Not available	Standard	OCU-KSC190M08-C
				—	✓	—			OCU-KSC190M08-D
				✓	✓	—			OCU-KSC190M08-CD
		OCU-KSC240M08	iCOOL 26D MHP	Base model. No options chosen.					OCU-KSC240M08
				✓	—	—	Not available	Standard	OCU-KSC240M08-C
				—	✓	—			OCU-KSC240M08-D
				✓	✓	—			OCU-KSC240M08-CD
		OCU-KSC280M08	iCOOL 29D MHP	Base model. No options chosen.					OCU-KSC280M08
				✓	—	—	Not available	Standard	OCU-KSC280M08-C
				—	✓	—			OCU-KSC280M08-D
				✓	✓	—			OCU-KSC280M08-CD
		OCU-KSC400M08	iCOOL 39D MHP	Base model. No options chosen.					OCU-KSC400M08
				—	✓	Standard	Not available	Standard	OCU-KSC400M08-D
		OCU-KSC420M08	iCOOL 43D MHP	Base model. No options chosen.					OCU-KSC420M08
				—	✓	Standard	Not available	Standard	OCU-KSC420M08-D

Series	Application	Base model	Former model name	Customization options					MODEL	
				Coating (C)	Heat recovery (D)	HP Fan (P)	Suction PRV (S)	Housing (H)		
iCOOL OCU	LT	OCU-KRC035L08	iCOOL 3 MP	Base model. No options chosen.					OCU-KRC035L08	
				✓	—	—	Not available	Standard	OCU-KRC035L08-C	
				—	✓	—			OCU-KRC035L08-D	
				—	—	✓			OCU-KRC035L08-P	
				✓	✓	—			OCU-KRC035L08-CD	
				✓	—	✓			OCU-KRC035L08-CP	
				—	✓	✓			OCU-KRC035L08-DP	
				✓	✓	✓			OCU-KRC035L08-CDP	
		OCU-KRC050L08	iCOOL 6 MP	Base model. No options chosen.					OCU-KRC050L08	
				✓	—	—	Not available	Standard	OCU-KRC050L08-C	
				—	✓	—			OCU-KRC050L08-D	
				—	—	✓			OCU-KRC050L08-P	
				✓	✓	—			OCU-KRC050L08-CD	
				✓	—	✓			OCU-KRC050L08-CP	
				—	✓	✓			OCU-KRC050L08-DP	
				✓	✓	✓			OCU-KRC050L08-CDP	
	OCU-KSC090L08	iCOOL 10 MP	Base model. No options chosen.					OCU-KSC090L08		
			✓	—	—	Not available	Standard	OCU-KSC090L08-C		
			—	✓	—			OCU-KSC090L08-D		
			✓	✓	—			OCU-KSC090L08-CD		
	OCU-KSC140L08	iCOOL 17D MP	Base model. No options chosen.					OCU-KSC140L08		
			✓	—	—	Not available	Standard	OCU-KSC140L08-C		
			—	✓	—			OCU-KSC140L08-D		
			✓	✓	—			OCU-KSC140L08-CD		
iCOOL SCU	MT	SCU-KSC160M08	iCOOL MAX 17D MHP	Base model. No options chosen.					SCU-KSC160M08	
				✓	—	Standard	Not available	Standard	SCU-KSC160M08-C	
				—	✓				SCU-KSC160M08-D	
				✓	✓				SCU-KSC160M08-CD	
		SCU-KSC190M08	iCOOL MAX 21D MHP	Base model. No options chosen.					SCU-KSC190M08	
				✓	—	Standard	Not available	Standard	SCU-KSC190M08-C	
				—	✓				SCU-KSC190M08-D	
				✓	✓				SCU-KSC190M08-CD	
	LT	SCU-KSC090L08	iCOOL MAX 10 MP	Base model. No options chosen.					SCU-KSC090L08	
				✓	—	Standard	Not available	Standard	SCU-KSC090L08-C	
				—	✓				SCU-KSC090L08-D	
				✓	✓				SCU-KSC090L08-CD	
iCOOL SE	MT	OCU-KRE025M05	iCOOL SE 2.5 MT	Base model. No options available.					OCU-KRE025M05	
		OCU-KRE045M05	iCOOL SE 4.5 MT						OCU-KRE045M05	
		OCU-KRE070M05	iCOOL SE 6.5 MT						OCU-KRE070M05	
		OCU-LRC100M08	iCOOL A2L 9 MHP	Base model. No options chosen.					OCU-LRC100M08	
				✓	—	Not available	Not available	Standard	OCU-LRC100M08-C	
				—	✓				OCU-LRC100M08-D	
				✓	✓				OCU-LRC100M08-CD	
		LT	OCU-KRE012L05	iCOOL SE 1.2 LT	Base model. No options available.					OCU-KRE012L05
	OCU-KRE022L05		iCOOL SE 2.2 LT	OCU-KRE022L05						
	OCU-KRE030L05		iCOOL SE 2.9 LT	OCU-KRE030L05						
	iCOOL LCU		MT	LCU-KRC045M08	PTXiAr 4.5 MHP	Base model. No options chosen.				
		LCU-KRC070M08		PTXiAr 7 MHP	Not available				✓	LCU-KRC045M08-H
Base model. No options chosen.					✓	LCU-KRC070M08				
LCU-KSC100M08		PTXiSs 10 MHP		Not available				✓	LCU-KRC070M08-H	
				Base model. No options chosen.				✓	LCU-KSC100M08	
LCU-KSC160M08		PTXiSs 17D MHP		Not available				✓	LCU-KSC100M08-H	
				Base model. No options chosen.				✓	LCU-KSC160M08	
LCU-KSC190M08		PTXiSs 21D MHP		Not available				✓	LCU-KSC160M08-H	
				Base model. No options chosen.				✓	LCU-KSC190M08	
LCU-KSC280M08		PTXiSs 29D MHP		Not available				✓	LCU-KSC190M08-H	
				Base model. No options chosen.				✓	LCU-KSC280M08	
LCU-KSC400M08		PTXiSs 39D MHP		Not available				✓	LCU-KSC280M08-H	
				Base model. No options chosen.				✓	LCU-KSC400M08	
LT		LCU-KRC020L08	PTXiAr 2 MP	Base model. No options chosen.					LCU-KSC400M08-H	
		LCU-KRC035L08	PTXiAr 3 MP	Not available				✓	LCU-KRC020L08	
				Base model. No options chosen.				✓	LCU-KRC020L08-H	
		LCU-KRC050L08	PTXiAr 6 MP	Not available				✓	LCU-KRC035L08	
				Base model. No options chosen.				✓	LCU-KRC035L08-H	
		LCU-KSC090L08	PTXiSs 10 MP	Not available				✓	LCU-KRC050L08	
				Base model. No options chosen.				✓	LCU-KRC050L08-H	
iCOOL WCU	MT	WCU-KRC045M08	WPTXiAr 4.5 MHP	Base model. No options chosen.					WCU-KSC090L08	
		WCU-KRC070M08	WPTXiAr 7 MHP	Not available				✓	WCU-KSC090L08-H	
				Base model. No options chosen.				✓	WCU-KRC045M08	
		WCU-KSC100M08	WPTXiSs 10 MHP	Not available				✓	WCU-KRC045M08-H	
				Base model. No options chosen.				✓	WCU-KRC070M08	
		WCU-KSC160M08	WPTXiSs 17D MHP	Not available				✓	WCU-KRC070M08-H	
				Base model. No options chosen.				✓	WCU-KSC100M08	
		WCU-KSC190M08	WPTXiSs 21D MHP	Not available				✓	WCU-KSC100M08-H	
				Base model. No options chosen.				✓	WCU-KSC160M08	
		WCU-KSC280M08	WPTXiSs 29D MHP	Not available				✓	WCU-KSC160M08-H	
				Base model. No options chosen.				✓	WCU-KSC190M08	
		WCU-KSC400M08	WPTXiSs 39D MHP	Not available				✓	WCU-KSC190M08-H	
				Base model. No options chosen.				✓	WCU-KSC280M08	
	LT	WCU-KRC020L08	WPTXiAr 2 MP	Base model. No options chosen.					WCU-KSC280M08-H	
		WCU-KRC035L08	WPTXiAr 3 MP	Not available				✓	WCU-KSC400M08	
				Base model. No options chosen.				✓	WCU-KSC400M08-H	
		WCU-KRC050L08	WPTXiAr 6 MP	Not available				✓	WCU-KRC020L08	
				Base model. No options chosen.				✓	WCU-KRC020L08-H	
		WCU-KSC090L08	WPTXiSs 10 MP	Not available				✓	WCU-KRC035L08	
				Base model. No options chosen.				✓	WCU-KRC035L08-H	